



Product Image Coming Soon

RAPID LOW TEMPERATURE CLOSED CUP FLASH POINT TESTER BPTL-239

RAPID LOW TEMPERATURE CLOSED CUP FLASH POINT TESTER

BPTL-239

Petroleum testing is the analysis during upstream, midstream, and downstream production processes of petroleum products. It is most commonly used to test petroleum product, its product components, byproducts of crude oil, fuel, natural gas, upstream oil and gas and other formats of petroleum.

Used in Petroleum Industry, PVC Pipe Industry.

BPTL-239 RAPID LOW TEMPERATURE CLOSED CUP FLASH POINT TESTER



Product Image Coming Soon

The instrument is specially suitable to determine different kinds of colored paints, oil paints, adhesives, solvents and petroleum products which the closed cup flash point is $-30^{\circ}\text{C} \sim 50^{\circ}\text{C}$. It can realize purpose of testing closed cup flash point rapidly and at low temperature. Test sample needed is less 2ml for each time (4ml for solid sample and semi-solid sample). The determination procedure is automatically completed except ignition. Test results can be printed automatically.

SPECIFICATIONS

Model	BPTL-239
Flash point measuring range	$-30^{\circ}\text{C} \sim +50^{\circ}\text{C}$
Temperature resolution	$\pm 0.1^{\circ}\text{C}$
Igniting device	Electric igniting gun
Cooling mode	Semiconductor (with cold water cycle at external connection)
Igniting source	Gas, LPG (or other civilian fuels)
Ambient temperature	$5^{\circ}\text{C} \sim 30^{\circ}\text{C}$
Relative humidity	(30~80) %
Total power consumption	$\leq 300\text{W}$
Dimension	490×520×390 mm
Net weight	25.5 kg



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com