



Product Image Coming Soon

DEMULSIBILITY CHARACTERISTICS TESTER (DESKTOP STRUCTURE) BPTL-260

DEMULSIBILITY CHARACTERISTICS TESTER (DESKTOP STRUCTURE) BPTL-260

Petroleum testing is the analysis during upstream, midstream, and downstream production processes of petroleum products. It is most commonly used to test petroleum product, its product components, byproducts of crude oil, fuel, natural gas, upstream oil and gas and other formats of petroleum.

Used in Petroleum Industry, PVC Pipe Industry.

BPTL-260 DEMULSIBILITY CHARACTERISTICS TESTER (DESKTOP STRUCTURE)



Product Image Coming Soon

The instrument is suitable to determine the water separability of petroleum oils and synthetic fluids. This instrument adopts small bath and desktop structure. The stirring paddle has good concentricity with cylinders. No tremble or touching the cylinder wall. It is easy to operate.

SPECIFICATIONS

Model	BPTL-260
Timing range	1s~9min59s
Stirring rate	(1500±15)r/min
Temperature range	(Room temp.+5~99.9)°C
Temperature control accuracy	±1°C
Ambient temperature	15°C~35°C
Relative humidity	≤ 85%
Total power consumption	≤1200W
Power supply	AC(220±10%)V, 50Hz
Dimension	500×340×720 mm
Net weight	22 kg



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com