



Product Image Coming Soon

ASH CONTENT TESTER (SEPERATELY DISPLAY) BPTL-273

ASH CONTENT TESTER (SEPERATELY DISPLAY) BPTL-273

Petroleum testing is the analysis during upstream, midstream, and downstream production processes of petroleum products. It is most commonly used to test petroleum product, its product components, byproducts of crude oil, fuel, natural gas, upstream oil and gas and other formats of petroleum.

Used in Petroleum Industry, PVC Pipe Industry.

BPTL-273 ASH CONTENT TESTER (SEPERATELY DISPLAY)



Product Image Coming Soon

The instrument is composed of a box-type heating furnace, a temperature control stand and an electric heating plate. It is small size and needs less land. The box-type furnace adopts all-in-one structure. Special fire-resistant material and heating components. The heating time is short and it has a long lifetime. Small size and good durability.

SPECIFICATIONS

| Model | BPTL-273 |
|---|--|
| Box-type heating furnace | |
| Rated temperature | 1000°C |
| Temperature rising time for empty furnace | ≤50 min |
| Power consumption for empty furnace | ≤800W |
| Furnace temperature uniformity | ≤15°C |
| Heat savings | ≤5kW.h |
| Thermocouple | WRN-010 |
| Rated power | 2.5 kW |
| Power supply | AC220V±10%, 50 Hz |
| Size of furnace chamber | 200×120×80 mm |
| Dimension | 575×3850×480 |
| Temperature control stand | |
| Maximum control temperature | 1200°C |
| Temperature controller: | DTW2001 |
| Thermocouple | WRN-010 |
| Rated controllable power | 5000W |
| Power supply | AC220V±20V,50Hz |
| Dimension | 500×300×235 mm |
| Electric heating plate | |
| Heating power | (1~6) grades, continuously adjustable. |
| Rated temperature | 400°C |
| Diameter of heating plate | Φ85mm |
| Rated power | 1500W |
| Power supply | AC(220±10%)V, 50Hz |

| | |
|-----------|---------------|
| Dimension | 280×250×90 mm |
|-----------|---------------|



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com