



BENCHTOP SHAKING INCUBATOR BSBT-1705

BENCHTOP SHAKING INCUBATOR BSBT-1705

BSBT-1705 BENCHTOP SHAKING INCUBATOR



Unique air flow technology adopts continuous flow fan technology, air stability, no turbulence, temperature is uniform

Cycle fan speed can be automatically controlled, it can avoid the samples volatile too fast due to cycle fan is too fast

Patented single-axis drive and balancing technology, running stable, low noise and low consumption

Adopts pneumatic support, transparent cover height can be adjustable to any position, convenient the operation

Colorful touch screen can continuously, accurately and real-time display temp, rotation speed and work time

The menu operation interface is easy to understand

Combine incubator, shaker functions together with small space

Patented overall design, transparent big view windows, dynamic master the culture effect

Shaking platform and chamber are made of stainless steel, anti-corrosion and easy to clean

Protection on instruments: Comply international standard secondary temp. limiter alarm system, alert the operator with sound and light alarms, ensure operator is safe without any accident

Protection on key components: Key components have over current, over temp., over load etc safety protection, it can prevent instruments accidents without precautions

Brushless DC motor, large start torque, wide speed adjustment, free maintenance

SPECIFICATIONS

Model	BSBT-1705
Speed Range	40-500 rpm
Temp. Range	RT+5 - 65°C
Temp. Control accuracy	0.1°C
Frequency accuracy	±1 rpm
Platform Dimension	250x250 mm
Inside height	195 mm
Overall Dimension	390Wx590Dx370H mm
N.W	32 Kg
Amplitude	4 mm
Running time	1 - 99h59min
Power requirement	AC 220 V / 50 Hz
Rated power	450 W
Standard configuration	250mlx8pcs



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com