



## COOLED SHAKING INCUBATOR BSCO-201

## COOLED SHAKING INCUBATOR BSCO-201

Equipped with precise cooling system and superior quality, low noise centrifugal fan that provides outstanding temperature uniformity ideal for most low temperature applications. Energy efficient, easy to clean design is an advantage for maximum process stability during microbiological tasks.

Used in Cell Culturing, Cell Aeration, Solubility Studies, Sample Preparation, Water Analysis, BOD Measurement, Plating, Breeding Experiments, Research Institutions, Universities, Colleges.

Also known as Cooled Shaking Incubator, Shaker Incubator, Laboratory Cooled Shaking Incubator.

## BSCO-201 COOLED SHAKING INCUBATOR



The electronic control of closed cycle adjustable heating system

Stainless steel interior and Electrostatic sprayed exterior

Call to restore function, without power supply

With strong influence of intermittent rapid heating system of .200 type and 100B type with air pressure regulating valve

Flexible and convenient, wide variety of detachable accessories

## SPECIFICATIONS

Model	BSCO-201
Speed Range	20-300 rpm
Standard Capacity	500 mlx3, 250 mlx4, 100 mlx5, 50 mlx5
Temperature	4°C~60°C
Temperature Accuracy	±0.1°C
Temperature Uniformity	±1°C
Shaking Speed Accuracy	±1 rpm
Timing Range	Optional
Motion	Orbital
Amplitude	26 mm
Tray	1
Platform Dimension	450x400 mm
Inner Dimension	508x458x360 mm
Overall Dimension	800x700x530 mm
Display	LCD
Weight	100 kg
Power	580 W
Power Supply	220 V, 60 Hz



**Biolab Scientific Ltd.**

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)