



FLUORESCENCE SPECTROPHOTOMETER BSFL-103

FLUORESCENCE SPECTROPHOTOMETER BSFL-103

Biolab Fluorescence spectrophotometers incorporate excellent wavelength accuracy and highly reliable optical performance to give highest sensitivity, reproducibility and accuracy. Xenon lamp minimizes photobleaching of samples thus maintaining sample integrity and produces high signal to noise ratio to give unmatched performance even with trace samples. Ergonomic with a longer lamp life, it gives more quality for your money.

Used in It serves a wide range of demanding clinical research, molecular biology, pharmaceutical and industrial applications..

BSFL-103 FLUORESCENCE SPECTROPHOTOMETER



Powerful Software Functions

SPECIFICATIONS

Model	BSFL-103
Wavelength Accuracy	±1 nm
Wavelength Repeatability	≤0.5 nm
Spectral Bandwidth	10 nm
Stability	Better than 1.5% per 10 min
Light Source	Xenon Lamp
Excitation Optical Filter	Interference optional filter of central wavelength at 365nm, optional interference filter of 25mm diameter of wavelength range 250-700nm
Excitation Wavelength Range	250-700 nm
Emission Wavelength Range	200-900 nm
Linearity	R ≥ 0.995
Response Time	0.1-4 sec
Monochromator	Czerny Turner Diffraction Grating
Gross Dimension (W/D/H)	380x440x240 mm
Weight (Net/Gross)	14 kg
Power	190 W
Power Supply	220V±22V, 50Hz±1Hz



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com