



## FLOOR STANDING SHAKING INCUBATOR BSFT-2304

# FLOOR STANDING SHAKING INCUBATOR BSFT-2304

## BSFT-2304 FLOOR STANDING SHAKING INCUBATOR



- Large LCD screen to display more data at same time
- R134a refrigerant, imported compressor and fan motor
- Big observation windows
- 304 Stainless steel chamber and platform, easy to clean.
- There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature measurement
- The parameters can be automatically stored in case of power failure, and it will continue run as presetting program after turn on
- Microprocessor PID controller for temperature and shaking speed with timing function

## SPECIFICATIONS

Model	BSFT-2304
Speed Range	40-300 rpm
Electrical Requirement	220 V 50 H
Amplitude	26 mm
Temperature Range	4 - 65°C
Display Resolution	0.1°C
Timing Range	0~5999 min
Power Consumption	2250 W
Platform Dimension	920x500 mm
Platform quantity	2 pcs



**Biolab Scientific Ltd.**

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)