



THREE TIER ORBITAL SHAKER BSOR-112

THREE TIER ORBITAL SHAKER BSOR-112

Our product is an accurately designed, microprocessor controlled with double Decker platform to save your valuable lab space. Three eccentric shaft balancing drive ensures shaking with uniform speed. Speed adjustment settings permit both gentle and vigorous shaking. Varieties of platforms are available for different glassware and vessels. Used in Stability, Dissolution Studies, Liquid Extractions, Protein Precipitation, Small Peptide Synthesis, Dilutions. Also known as Laboratory Orbital Shaker.

BSOR-112 THREE TIER ORBITAL SHAKER



PID controller.

Soft shaking mode, stable and reliable operation.

Eight self-compiled programs, with different speed and time setting.

Automatic operation, auto-stop, timing, time display, parameters memory and recovery function.

Automatic power-off protection system when the motor is overheating and temperature is out of control.

SPECIFICATIONS

Model	BSOR-112
Speed Range	50~250 rpm
Maximum Configuration	250 mlx450 or 500 mlx324 or 1000 mlx168
Shaking Speed Accuracy	±1 rpm
Timing Range	0~500 h
Motion	Orbital
Vibrational Amplitude (mm)	Φ50 mm
Circulation Mode	Natural convection
Drive Mode	Multi-dimensional driving
Shaking Plate Quantity	6 pcs
External Material	Cold-rolled steel with anti-bacterial power coating
Platform Dimension	1080x680 mm
Overall Dimension	1470x1110x1320 mm
Package Dimension	1570x1210x1470 mm
Display	LCD
Weight	950 kg
Power	1100 W
Standard Configuration	250 mlx225, 500 mlx162
Power Supply	AC110V/220V±10%,50/60Hz



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com