PRODUCT CATALOG

ORBITAL SHAKER BSOT-602

CE ISO9001 CERTIFIED

www.biolabscientific.com

ORBITAL SHAKER BSOT-602

Our product is an accurately designed, microprocessor controlled with double Decker platform to save your valuable lab space. Three eccentric shaft balancing drive ensures shaking with uniform speed. Speed adjustment settings permit both gentle and vigorous shaking. Varieties of platforms are available for different glassware and vessels.
Used in Stability, Dissolution Studies, Liquid Extractions, Protein Precipitation, Small Peptide Synthesis, Dilutions.
Also known as Laboratory Orbital Shaker.

BSOT-602 ORBITAL SHAKER

- Microprocessor PID controller, with timing function
- Stainless-steel or alnico plate, non-eroding and easy clean
- DC Brushless motor with long using life, wide speed control with long using life, wide speed control
- The alarm will get off when the real shaking speed is 10% different with setting value, and motor will stop automatically
- Speed controller ensures smooth start /stop which can prevent the liquid spill to damage the equipment
- LCD screen, programmable controller. (18periods with temperature, speed and timing) and over-temperature alarm

SPECIFICATIONS

Model	BSOT-602
Speed Range	50-250 rpm
Temperature	No heating function
Shaking Orbit	20 mm
Timing Range	0~5999 min
Motion	Orbital
Operation	Continuous/Timed
Platform Dimension	280x270 mm
Power	60 W
Platform optional	Universal platform or Spring wire racks (Default)
Power Supply	220V, 50Hz

Biolab Scientific Ltd.
3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com