

# PRODUCT CATALOG



# **REAL-TIME MINI THERMAL CYCLER BTHC-203**





www.biolabscientific.com

### **REAL-TIME MINI THERMAL CYCLER BTHC-203**

Mini-PCR works interchangeably with standard PCR assays, reagents, and consumables. It is portable, user friendly, small in size and easy to program with an intuitive user interface. It is benefit for students to understand with the animation presentation capabilities of the PC operating software.

Used in Incubation, Research, Development, Food Science, Pharmaceutical, Life Science, Animal Diagnostics, Analytical Laboratories, Molecular biology, Gene amplification, Gene Expression.

Also known as Laboratory Mini PCR, Mini PCR Machine, Laboratory Mini PCR Machine.

### **BTHC-203 REAL-TIME MINI THERMAL CYCLER**



Petlier technology: Solid-state, thermoelectric heating nad cooling uni for improved cotrol and durability

Bottom detection system provides greater accuray and sensitivity of measurements High-powered photomultipiler provides sensitive detection

Long life LED excitation light source does not spend maintenance or preheating Hot-lid feature allows oil-free operation

Advanced PID control ensure the accuracy of temperature control

#### **SPECIFICATIONS**

| Model                | BTHC-203   |  |  |  |  |
|----------------------|--|--|--|--|--|
| Temperature Range    | 4~100°C  |  |  |  |  |
| Ambient Temperature  | Operation Temp: 15-30°C; Storage Temp: 10-60°C   |  |  |  |  |
| Ambient Humidity     | Operation Humidity: 15-90% Relative Humidity; Storage Humidity: 5-95% Relative Humidity        |  |  |  |  |
| Max. ramp rate       | 3°C / s  |  |  |  |  |
| Reaction volume      | 10-150 µL  |  |  |  |  |
| Block Formats        | 8 Wells  |  |  |  |  |
| Block Material       | Peltier  |  |  |  |  |
| High Resolution Melt | Supported Resolution to 0.5°C  |  |  |  |  |
| Multiplexing         | Detect up to 2 dyes simultaneously, 470 / 520 nm(SYBR / FAM) and 565 / 625 nm(ROX / Texas Red) |  |  |  |  |
| Thermal Uniformity   | ±0.2°C   |  |  |  |  |
| Thermal Accuracy     | ±0.2°C   |  |  |  |  |
| Light Source         | High power LED   |  |  |  |  |
| Detector             | Photediode   |  |  |  |  |
| PC Operation system  | WIN2000  |  |  |  |  |
| XP                   | WIN7   |  |  |  |  |
| WIN8                 | Dimension (WxDxH)  |  |  |  |  |
| 190x205x98 mm        | Weight   |  |  |  |  |
| 2.1 kg               | Power Supply   |  |  |  |  |

### **OPTIONAL ACCESSORIES**

| Accessory Code | Name    | Description                                  | Excitation Wavelength(450-590 nm)                                   | Emission Wavelength  | Detected Fluorescence   |
|----------------|---------|--|---|--|---|
| 5200808006     | Block A | 48x0.2 ml (4<br>channels; auto hot-<br>lid)  | Standard Channels: F1:470 nm;<br>F2:523 nm; F3:543 nm; F4:571<br>nm | Standard Channels:<br>F1:525 nm; F2:564<br>nm; F3:584 nm;<br>F4:612 nm | F1: FAM; SYBR Green I F2:<br>HEX; VIC F3: TAMRA; JOE;<br>Cy3 F4: TEXAS-RED; ROX |
| 5200808007     | Block B | 48x0.2 ml (2<br>channels; manual<br>hot-lid) | F1:470 nm; F2:564 nm  | F1: 525 nm; F2: 564<br>nm  | F1: FAM; SYBR Green I F2:<br>HEX; VIC   |



Biolab Scientific Ltd. 3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada Email: info@biolabscientific.com | Website: www.biolabscientific.com