



TUBE ROLLER BTUR-103

TUBE ROLLER BTUR-103

The versatile, end-over-end tube roller and Rotators are designed for mixing samples in both a vertical and horizontal plane. They can be placed in an environment temperature ranges from 5 to 40° and the rotation speed is adjustable, from 0 to 99 rpm. Tube Rollers, Rotators and Rocker are designed to deliver salient performance, accuracy, and reproducible results for all your application needs.

Used in Industrial, Clinical Laboratories, Academic Facilities, Environmental Applications, Food Technology, Wastewater Facilities.

Also known as Tube Roller, Roller, Laboratory Roller.

BTUR-103 TUBE ROLLER



Compact and firm designed, simple operation, LED display time and speed.

Two types selectable - rolling type and rolling & rolling type and rolling & swinging type. Continuous working mode, safe and stable.

With stable performance motor, operation speed adjustable, max. speed to 80rpm. Low noise, long using life.

Can compatible with different size of tubes. Large range of application.

SPECIFICATIONS

Model	BTUR-103
Speed Range	5 ~ 80 rpm
Operation Mode	Rolling and Fluctuation
Amplitude	25 mm
Roller Quantity	6
Roller Length	280 mm
Max. Load	4 kgs
Time Range	1min~99h59min
Voltage	AC 100~230V, 50/60 Hz
Power	25 W
Fuse	250V, 1A, Φ 5x20
Dimension	W.450 x D.260 x H.120 mm



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com