



## DIGITAL DISPLAY ULTRASONIC CLEANER BULC-305

# DIGITAL DISPLAY ULTRASONIC CLEANER BULC-305

Digital Display Ultrasonic Cleaner uses frequency of 40Khz for cleaning the lab equipments.  
Also known as Digital ultrasonic cleaner, Ultrasonic cleaning bath, Ultrasonic cleaning tank.

## BULC-305 DIGITAL DISPLAY ULTRASONIC CLEANER



Digital display and control  
Industrial high Q transducers, cleaning conversion efficiency is higher  
No stud- welding technology, Cleaning effect is better  
MCU SWEEP multi frequency ultrasonic generator output, frequency sweep drive ultrasonic cleaning effect more powerful  
MHC heating system, maximum temperature is up to 80°C  
All stainless steel material inner tank is made by punching SUS304 1.0mm  
2500V high voltage test to ensure the product safety, strict production, aging production quality control

## SPECIFICATIONS

Model	BULC-305
Capacity	5.0 L
Working frequency	40 Khz
Ultrasonic Power	120 W
Heating power	200 W
Timing time	1- 99 mins
Temperature range	0- 80°C
Cover	Yes
Drain valve	No
Washing basket	Optional
Inner tank dimension	240x135x100 mm
Packing size	342x240x355 mm
Gross weight	5.4 Kg
Power Supply	220V+ 10% 50Hz/60Hz 110V+ 10% 50Hz/60Hz



**Biolab Scientific Ltd.**

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)