



MINI VACUUM PUMP BVAP-201

MINI VACUUM PUMP BVAP-201

The liquid suction filtration vacuum pump series is mainly used for separation of culture fluid and culture tissue after biochemical culture, extraction of cell culture waste liquid, and suction of various waste liquids in the laboratory. Different flow specifications are available to meet more experimental needs, and it is the best experimental assistant indispensable for the laboratory aseptic workstation.

Used in Extraction of cell culture waste liquid, Laboratory, Research, Medical, Separation of culture fluid, Culture tissue, Biochemical culture..

Also known as Laboratory Mini Vacuum Pump.

BVAP-201 MINI VACUUM PUMP

Pumping filter brackets are equipped on both sides of the instrument, easy to store and select the suction filter accessories

Standard equipped with multi-function suction filter handle and 5 kinds of suction head accessories to meet more requirements of suction experiments

Sealed waste liquid bottle cap design, quick-insertion sealing joint, convenient to get out of the fuselage bottle and clean up waste liquid

Normally open control mode and foot switch control mode, to meet more experimental requirements

Waste liquid bottle, suction filter fittings and dish filter can all be used for autoclave sterilization

There is a liquid level protection switch in the waste liquid bottle to prevent the waste liquid from overflowing and being sucked into the pump chamber to ensure no troubles in suction filtration

There is a PTFE dish shape filter between the bottle and the pump to protect the environment from harmful gas pollution

The self-locking quick connector can be quickly and easily separated from the pipeline, which is convenient for safely cleaning the waste bottle

Built-in high quality oil-free vacuum pump, no maintenance, low noise and long life

SPECIFICATIONS

| | |
|------------------------------------|----------------|
| Model | BVAP-201 |
| Max. Flow rate | 8 L/min |
| Vacuum degree | -0.06 Mpa |
| Vacuum display mode | Vacuum gauge |
| Negative pressure adjustment range | 0~-0.08 Mpa |
| Waste liquid bottle capacity | 1000 mL |
| Voltage | DC24 V 0.8 A |
| Power | 8 W |
| Dimension (WxDxH) | 130x288x350 mm |
| Net weight | 1.6 kgs |

ACCESSORIES

| Accessory Code | Name | Material | Quantity |
|----------------|---|------------|----------|
| 5900606006 | Hand-held operator | POM | 1 |
| 5900606007 | Eight-channel retractable tip plastic extraction head | POM | 1 |
| 5900606008 | Eight channel stainless steel extraction head | POM+SUS304 | 1 |

| | | | |
|------------|--|------------|---|
| 5900606009 | Single channel plastic extraction head | POM | 1 |
| 5900606010 | Single channel retractable tip plastic head | POM | 1 |
| 5900606011 | Single channel stainless steel extraction head | POM+SUS304 | 1 |



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada
Email: contact@biolabscientific.com | Website: www.biolabscientific.com