



## VERTICAL LAMINAR AIRFLOW

## VERTICAL LAMINAR AIRFLOW

Compact design required for operations in an ultra clean, dust free environment. Ideal for laboratory applications where product protection is required. Small size saves precious laboratory space. Contains ultra thin filter including static pressure box without separator. Larger space permits working with laboratory equipments within the workspace. Used in Electronic sectors, Industrial sectors, Medical, Pharmaceutical, Healthcare.

Also known as Tissue Culture Hood, Laminar Air Flow Cabinet, Laboratory Laminar Flow, Laboratory Laminar Air Flow, Laminar Flow Cabinet, Minimal-Turbulence Air Flow, Laminar Flow Cabinet, Laminar Flow Hood, Laminar Flow.

## 100 VERTICAL LAMINAR AIRFLOW



Microprocessor controller

Pre-filter: Polyester fiber, washable

UV Lamp: Emission of 253.7 nanometers

Waterproof socket: Two, total load  $\leq 500W$

Display Airflow velocity, UV timer, UV work time, system work time, real time

## SPECIFICATIONS

Model	BLVR-101	BLVR-102
Type	Vertical Laminar Flow	
Airflow Velocity	Average of 0.3~0.5m/s	
HEPA Filter	99.999% efficiency at 0.3 $\mu$ m	
Pre-filter	Polyester fiber, washable	
Work Surface Height	750mm	
Main Body Material	Cold-rolled steel with anti-bacteria powder coating	
Work Table Material	304 stainless steel	
Side and Front Window Material	5mm toughened glass, anti-UV	
UV Lamp	30 Wx1 Emission of 253.7 nanometers	40 Wx1 Emission of 253.7 nanometers
LED Lamp	12W x1	16W x1
Display	LCD display	
Front Window	Motorized	
Max Opening	430 mm	
Caster	Universal caster with leveling feet	
Waterproof Socket	Two, total load $\leq 500W$	
Standard Accessory	LED lamp, UV lamp x2, Base stand, Gas Tap, Waterproof socket x2	
Optional Accessory	Electric height adjustable base stand	
Internal Size	1200Wx645Dx610 mm	1700Wx645Dx610 mm
External Size	1300Wx750Dx2040H mm	1800Wx750Dx2040H mm
Packaging Size	1460x1070x1650mm	1960x970x1600mm
Gross Weight	228kg	306kg
Noise	<65dB	

Consumption	400 W	450 W
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz	AC220V±10%, 50/60Hz; 110V±10%, 60Hz



BLVR-101



BLVR-102

## 200 VERTICAL LAMINAR AIRFLOW



Microprocessor controller  
Pre-filter: Polyester fiber, washable  
UV Lamp: Emission of 253.7 nanometers

## SPECIFICATIONS

Model	BLVR-201	BLVR-202	BLVR-203	BLVR-204
Type	Vertical Laminar Flow			
Air Flow Velocity	Average of 0.3~0.5m/s, air speed adjustable.		Average of 0.3~0.45m/s, air speed adjustable.	
HEPA Filter	99.995% efficiency at 0.3μm			
Pre-filter	Polyester fiber, washable			
Work Surface Height	/	660mm	750mm	
Max Opening	/	490mm	400mm	
Front Window	/	Manual, 5mm toughened glass, anti-UV		
UV Lamp	15Wx1 Emission of 253.7 nanometers	20Wx1 Emission of 253.7 nanometers		40Wx1 Emission of 253.7 nanometers
illuminating Lamp	Fluorescent lamp 8W*1	LED lamp 8W*1	LED lamp 12W*1	LED lamp 16W*1
Display	LED Display		LCD Display	
Main Body Material	Cold-rolled steel with anti-bacteria powder coating			
Work Table Material	304 stainless steel	/	304 stainless steel	
Caster	/	Universal wheel with leveling feet		
Standard Accessory	Fluorescent lamp; UV lamp x2; Water & gas tap.	LED lamp; UV lamp x2; Base stand;	LED lamp; UV lamp x2; Base stand.	

Optional Accessory	/	Electric height adjustable base stand		
Noise	<65dB			
Internal Size	630Wx375Dx615H mm	800x530Dx540H mm	935Wx530Dx650H mm	1335Wx530Dx650H mm
External Size	680Wx410Dx1160 mm	802Wx650Dx1550 mm	1060Wx620Dx1850 mm	1460Wx620Dx1850 mm
Package Size	840Wx560Dx1380H mm	960Wx800Dx1800H mm	1240Wx900Dx1350H mm	1640Wx900Dx1350H mm
Gross Weight	50kg	116kg	185kg	231kg
Consumption	160W	350W	150W	250W
Power Supply	AC220V±10%, 50/60 Hz; 110V±10%, 60Hz			



BLVR-201



BLVR-202



BLVR-203



BLVR-204

## 300 VERTICAL LAMINAR AIRFLOW



Microprocessor controller

Double side work bench, operators can sit face to face

Pre-filter: Polyester fiber, washable

UV lamp: Emission of 253.7 nanometers

## SPECIFICATIONS

Model	BLVR-301	BLVR-302
Type	Vertical Laminar Flow	
Air Flow Velocity	Average of 0.3~0.5m/s	
HEPA Filter	99.995% efficiency at 0.3µm	
Pre-filter	Polyester fiber, washable	
Work Surface Height	750mm	
Max Opening	310mm	
Front Window	Manual, 5mm toughened glass, anti-UV	
UV Lamp	20W*1 Emission of 253.7 nanometers	30W*1 Emission of 253.7 nanometers
LED Lamp	12W*1	16W*1
Display	LCD display	
Main Body Material	Cold-rolled steel with anti-bacteria powder coating	
Work Table Material	304 stainless steel	

Caster	Universal caster with leveling feet	
Standard Accessory	LED lamp, UV lamp x2, Base stand.	
Optional Accessory	Electric height adjustable base stand	
Noise	<65dB	
Internal Size	940Wx560Dx545H mm	1340Wx560Dx545Hmm
External Size	1040Wx660Dx1770 mm	1440Wx660Dx1770 mm
Package Size	1190Wx890Dx1340H mm	1590Wx890Dx1340H mm
Gross Weight	150kg	186kg
Consumption	350W	600W
Power Supply	AC220V±10%, 50/60 Hz; 110V±10%, 60 Hz	



BLVR-301



BLVR-302

## 300 VERTICAL LAMINAR AIRFLOW



ETL certified, Satisfy North American market.  
With memory function in case of power-failure.  
Audio and visual alarm(Abnormal airflow velocity).  
Interlock function: UV Lamp and blower LED Lamp.

## SPECIFICATIONS

Model	BLVR-303	BLVR-304	BLVR-305
Type	The ETL certified vertical laminar flow cabinet	The ETL certified vertical laminar flow	
Airflow Velocity	Average of 80~99 fpm		
HEPA Filter	One,99.995% efficiency at 0.3μm		
Pre-Filter	Polyester fiber		
Work Surface Height	750~1010mm		
Max Opening	480mm		
Working area Material	304 stainless steel		
Main Body Material	1.2mm Cold-rolled steel with anti-bacteria powder coating.		
Front Window Material	Motorized, 5mm toughened glass, anti-UV		
Waterproof Sockets	One socket (Double type), America standard, Max.Power: 500W		

UV Lamp	18W x1	30W x1
LED Lamp	10W x1	14W x1
Display	LCD Display	
Illumination	≥300lx	
Noise	≤68dB(A)	
Standard Accessory	Manually height adjustable base stand; LED lamp; UV lamp; Wind speed sensor; Waterproof socket.	
Internal Size	700Wx575Dx625H mm	1000Wx575Dx625H mm
External Size	800x700x(2090~2340)mm	1100x700x(2090~2340)mm
Package Size	940Wx970Dx1560H mm	1440Wx970Dx1560H mm
Gross Weight	190kg	230kg
Consumption	750W	950W
Power Supply	110V±10%V, 60HZ	

Model	BLVR-306	BLVR-307
Type	The ETL certified vertical laminar flow	
Airflow Velocity	Average of 80~99 fpm	
HEPA Filter	One,99.995% efficiency at 0.3μm	
Pre-Filter	Polyester fiber	
Work Surface Height	750~1010mm	
Max Opening	480mm	
Working area Material	304 stainless steel	
Main Body Material	1.2mm Cold-rolled steel with anti-bacteria powder coating.	
Front Window Material	Motorized, 5mm toughened glass, anti-UV	
Waterproof Sockets	One socket (Double type), America standard, Max.Power: 500W	
UV Lamp	40W x1	
LED Lamp	18W x1	22W x1
Display	LCD Display	
Illumination	≥300lx	
Noise	≤68dB(A)	
Standard Accessory	Manually height adjustable base stand; LED lamp; UV lamp; Wind speed sensor; Waterproof socket.	
Internal Size	1400Wx575Dx625H mm	1700Wx575Dx625H mm
External Size	1500x700x(2090~2340)mm	1800x700x(2090~2340)mm
Package Size	1640Wx970Dx1560H mm	1940Wx970Dx1560H mm
Gross Weight	280kg	320kg
Consumption	950W	1150W
Power Supply	110V±10%V, 60HZ	



BLVR-303



BLVR-304



BLVR-305



BLVR-306



BLVR-307



**Biolab Scientific Ltd.**

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: [info@biolabscientific.com](mailto:info@biolabscientific.com) | Website: [www.biolabscientific.com](http://www.biolabscientific.com)