



MANUAL OPERATION TABLE

MANUAL OPERATION TABLE

Manual Operation table are suitable for various operation tables conducted by medical unit. The OR table and accessories are ergonomic and can be used across multiple disciplines. Various actions are controlled by hydraulic pneumatic system. 360° rotation helps every surgical requirement.

Used in Medical unit, Surgery, Operation theatre, cardiovascular, pediatric, gynecology, abdominal, gall bladder, plastic surgery and more.

Also known as Manual surgical table, Manual OR Table, Manual operating table.

BOPT-201 MANUAL OR TABLE



The super low level design can enable doctor to conduct operation sitting by operating table

Adopt electric hydraulic double cylinder elevating with stable performance

Import rotor and Electromagnetic valve

Imported sealing ring and is durable

The base seat and upright column covering are made of high quality 304 stainless steel which is anti-corrosive and can be easily cleaned

Electric braking control which is easily for moving operating table

SPECIFICATIONS

Model	BOPT-201
Table Length	2100±50 mm
Table Width	480±20 mm
Height Adjustment	(800~1050) ±20 mm
Head board upwards	≥45°
Head board downwards	≥90°
Backboard upwards	≥80°
Backboard downwards	≥30°
Waist board lifting	100+20 mm
Leg board downwards	≥90°
Back Board Upwards	≥80°
Back Board Downwards	≥30°
Standard Accessories	A Pair of Shoulder/Waist Support, A pair of Arm Support, A pair of leg Plate, A screen

BOPT-202 MANUAL OR TABLE



Various actions are controlled by hydraulic pneumatic system and mechanical driven system

Head plate can be exchanged with leg plate which can fulfill the needs of C type arm complete examination, X-ray photography

Imported Y type sealing ring is durable

The table surface adopts quality carbon plastic plate, the mattress adopts high density memory sponge and is once formed, with no seam

Quality stainless steel 304 is used for base plate, column shield and rails on both sides of the table, easy for cleaning and sterilization

Foot treadle brake device which is easily for moving operating table

SPECIFICATIONS

Model	BOPT-202
Table Length	2000±50 mm
Table Width	500±20 mm
Height Adjustment	(700~950) ±50 mm
Left tilt	≥15°
Right tilt	≥15°
Trendelenburg	≥15°
Reverse trendelenburg	≥15°
Head board upwards	≥30°
Head board downwards	≥90°
Backboard upwards	≥60°
Backboard downwards	≥20°
Leg board downwards	≥90°

BOPT-203 MANUAL OR TABLE



Various actions are controlled by hydraulic pneumatic system

All movements of the table are manipulated using the operating handle under the head plate

Imported Y type sealing ring is durable

The table surface adopts quality carbon plastic plate which is easily for conducting X-ray examination, equipped with coincidence rail

Both sides of the bed rail for the high quality 304 stainless steel

The base adopts imported carbon cloth which can be easily cleaned and sterilized

The mattress is wrapped with imported artificial leather. High-density memory sponge is formed in one piece, with no seam

Foot treadle brake device which is easily for moving operating table

SPECIFICATIONS

Model	BOPT-203
Table Length	2000±50 mm
Table Width	500±20 mm
Height Adjustment	(700~950) ±50 mm
Left tilt	≥15°
Right tilt	≥15°
Trendelenburg	≥20°
Reverse trendelenburg	≥15°
Head board upwards	≥30°
Head board downwards	≥90°
Backboard upwards	≥70°
Backboard downwards	≥15°
Waist board lifting	≥70°
Leg board downwards	≥90°
Leg board outwards	≥180°
Main Voltage AC	220V±22V, 50Hz±1Hz
Input Power VA	150±10%

BOPT-204 MANUAL OR TABLE



Imported LINAK motor various actions are controlled by remote controller

The table, base seat and upright column covering are made of high quality 304 stainless steel, which is anti-corrosive and can be easily cleaned

The mattress adopts high density memory sponge and is once formed, with no seam

Whole stainless steel hidden auxiliary table with flexible extension and retraction

Equipped with stainless steel sewage basin and other accessories

Foot treadle brake device which is easy for moving obstetric table

SPECIFICATIONS

Model	BOPT-204
Table Length	2000±50 mm
Table Width	600±20 mm
Height Adjustment	(700~950) ±50 mm
Working area length/width	520x500 mm
Trendelenburg/Rev-Trend	≥10°/≥12°
Backboard upwards	≥50°
Standard Accessory	A pair of arm support, a pair of leg support, a pair of foot pedal, a pair of arm rods, a stainless steel sewage basin, a handheld remote, controller
Main Voltage AC	220V±22V, 50Hz±1Hz
Input Power VA	150±10%



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com