



WALK IN FUME HOOD

WALK IN FUME HOOD

Biolab Scientific offers a wide range of Walk in fume hood to suit every specific application of the user. It is floor mounted, dual layered, designed to isolate a work process within a larger workspace so as to not cross contaminate between various applications.

800 WALK IN FUME HOOD



With memory function in case of power-failure.

Operators are available to walk into the fume hood to operate if need.

Large room exhaust system, suitable for large laboratory instruments and equipment.

SPECIFICATIONS

Model	BFSD-801	BFSD-802	BFSD-803
Inflow Air Velocity	0.3~0.8 m/s		
Exhaust Airflow Volume	1150m³/h	1500m³/h	1850m³/h
Max Opening	1300mm		
Vibration	Amplitude≤5μm		
Front Window	Manual, 5mm toughened glass, height adjustable		
Exterior Material	1.0mm cold-rolled steel with bacteria powder coating.		
Interior Material	Compact laminate board with good acid and alkali resistance function		
Fluorescent Lamp	12Wx2	16Wx2	
Illumination	≥800Lux		
Sockets	Total load of 4 waterproof sockets: ≤500W		
Noise	≤62dB		
Standard Accessory	External blower, LED lamp, Water tap, Gas tap, PP cup sink, Remote control water valve, Remote control gas valve, Waterproof sockets x4, 4.3 meters φ300mm PVC exhaust duct.		
Internal Size (WxDxH)	980x550x1670mm	1280x550x1670mm	1580x550x1670mm
External Size (WxDxH)	1200x800x2250mm	1500x800x2250mm	1800x800x2250mm
Main body Package Size(WxDxH)	1400x1050x2450mm	1710x1050x2450mm	2010x1050x2450mm
Exhaust Blower Package Size(WxDxH)	970x810x720mm	1040x890x710mm	
Gross Weight	300kg	340kg	390kg
Consumption	400 W	500 W	800 W
Power Supply	AC220V±10%, 50/60Hz; 110 V±10%, 60Hz		



BFSD-801



BFSD-802



BFSD-803



Biolab Scientific Ltd.

3660 Midland Avenue, Suite 300, Toronto, Ontario M1V 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com