



DOUBLE DOOR FREEZER

DOUBLE DOOR FREEZER BEZ1X1

-40°C BIOMEDICAL FREEZER



Microprocessor control, ensure good inner temperature uniformity, accuracy is 0.1°C
HC green refrigerant is energy-saving and environmentally friendly.

Wide available voltage range: 220V±10%.

Security

Safety door lock and controller password to prevent unauthorized access.

Built-in backup battery to display temperature and alarms when power failure or system error.

Visual and audible alarm system.

Inner doors to prevent cold air from leaking out when the outside door is opening.

Power failure protection: turn-on delay of the cooling system after power failure

SPECIFICATIONS

Model	BEZ1X1
Old Model	BFUR-40-304
Temperature Range	-20 ~ -40°C
Ambient Temperature	10~32°C
Capacity (L / Cu. Ft.)	328 / 11.58
Interior Dimensions (WxDxH) mm	508x455x1393
Exterior Dimensions (WxDxH) mm	673x676x1886
Weight	113 kgs
Noise	48 dB
Controller	Microprocessor
Display	Digital
Sensor	NTC
Voltage and Frequency	220V±10%, 50/60Hz
Power	330W
Electric Current	1.54 A
Power Consumption (kWh/24h)	6.5
High / Low Temp. Alarm	Yes
Power Failure Alarm	Yes, 8h
Sensor Error Alarm	Yes
Controller Error Alarm	Yes
Door Ajar Alarm	Yes
Refrigeration Type	Direct Cooling
Defrost	Manual
Compressor (Brand/pcs)	CUBIGEL / 1
Refrigerant / Weight	R290 / 78g
Door (pcs)	Foamed Solid Door / 1
Inner Doors (pcs)	Coated Steel Door / 5
Adjustable Shelves (pcs)	4
Interior Cabinet Material	Coated Steel
Exterior Cabinet Material	Coated Steel
Insulation Material	PURF (82.5mm)

Door Lock	Yes
Test Hole (pcs)	1
Castors (pcs)	4
Remote Alarm Port	Yes
USB Data Download Port	Optional
RS485 Port	Optional
Temperature Datalogger	Optional
Temperature Printer	Optional
Package	Carton box with pallet
Shipping Weight	133 kgs
Shipping Size (WxDxH) mm	760x760x2000
Shipping Volume	1.16 CBM
Alt Name	-40°C Biomedical Freezer



FEATURES

Microprocessor control, ensure good inner temperature uniformity, accuracy is 0.1°C

HC green refrigerant is energy-saving and environmentally friendly.

Wide available voltage range: 220V±10%.

Security

Safety door lock and controller password to prevent unauthorized access.

Built-in backup battery to display temperature and alarms when power failure or system error.

Visual and audible alarm system.

Inner doors to prevent cold air from leaking out when the outside door is opening.

Power failure protection: turn-on delay of the cooling system after power failure.

Controller error protection: the cooling system will remember the normal working cycle and keep working depending on this memory when the controller or two sensors failed.

Humanized design

Adjustable shelves for easy storage.

Castors with stoppers for easy moving and fixation.

APPLICATIONS

The -40°C medical deep freezers are designed to store vaccines, blood plasma, reagents, and many other biological materials which are widely used in research institutions, clinics, and medical fields.

DOUBLE DOOR FREEZER BEZ111

-25°C DOUBLE-DOOR BIOMEDICAL FREEZER



Microprocessor control, ensure good inner temperature uniformity, accuracy is 0.1°C

Double outside doors and two independent freezer chambers.

HC green refrigerant is energy-saving and environmentally friendly.

Wide available voltage range: 220V±10%.

Security

Safety door lock and controller password to prevent unauthorized access.

Built-in backup battery to display temperature and alarms when power failure or system error.

Visual and audible alarm system.

Power failure protection: turn-on delay of the cooling system after power failure.

SPECIFICATIONS

Model	BEZ111
Old Model	BFRZ-25-404
Temperature Range	-10 ~ -25 °C
Ambient Temperature	10~32°C
Capacity (L/Cu. Ft.)	358 / 12.64 (179x2 / 6.32x2)
Interior Dimensions (WxDxH) mm	466x636x625x2
Exterior Dimensions (WxDxH) mm	720x830x1870
Weight	138 kgs
Controller	Microprocessor
Display	Digital
Sensor	NTC
Voltage and Frequency	220V±10%, 50/60Hz
Power	310 W
Electric Current	3 A
Power Consumption (kWh/24h)	5.5
High / Low Temp. Alarm	Yes
Power Failure Alarm	Yes, 8h
Sensor Error Alarm	Yes
Controller Error Alarm	Yes
Door Ajar Alarm	Yes
Abnormal Ambient Temp. Alarm	Yes
Refrigeration Type	Direct Cooling
Defrost	Manual
Compressor (Brand/pcs)	CUBIGEL / 2
Refrigerant / Weight	R290 / 80g
Door (pcs)	Foamed Solid Door / 2
Fixed Shelf (pcs)	4
Drawer (pcs)	12
Interior Cabinet Material	Coated Steel
Exterior Cabinet Material	Coated Steel
Insulation Material	PURF (Φ95mm)

Door Lock	Yes
Test Hole (pcs)	2
Castors (pcs)	4
Leveling Feet (pcs)	2
USB Data Download Port	Yes
Remote Alarm Port	Yes
RS485 Port	Optional
Temperature Datalogger	Optional
Temperature Printer	Optional
Package	Carton box with pallet
Shipping Weight	178 kgs
Shipping Size (WxDxH)	780x920x2000
Shipping Volume	1.51 CBM
Alt Name	-25°C Double-door Biomedical Freezer



FEATURES

Microprocessor control, ensure good inner temperature uniformity, accuracy is 0.1°C

Double outside doors and two independent freezer chambers.

HC green refrigerant is energy-saving and environmentally friendly.

Wide available voltage range: 220V±10%.

Security

Safety door lock and controller password to prevent unauthorized access.

Built-in backup battery to display temperature and alarms when power failure or system error.

Visual and audible alarm system.

Power failure protection: turn-on delay of the cooling system after power failure.

Controller error protection: the cooling system will remember the normal working cycle and keep working depending on this memory when the controller or two sensors failed.

Humanized design

Drawers for easy storage.

Casters with stoppers for easy moving and fixation.

APPLICATIONS

The -25°C medical deep freezers are designed to store vaccines, blood plasma, reagents, and many other biological materials which are widely used in research institutions, clinics, and medical fields.

DOUBLE DOOR FREEZER BEZ1J1

-25°C DOUBLE-DOOR BIOMEDICAL FREEZER



Microprocessor control, ensure good inner temperature uniformity, accuracy is 0.1°C

Double outside doors and two independent freezer chambers.

HC green refrigerant is energy-saving and environmentally friendly.

Wide available voltage range: 220V±10%.

Security

Safety door lock and controller password to prevent unauthorized access.

Built-in backup battery to display temperature and alarms when power failure or system error.

Visual and audible alarm system.

Power failure protection: turn-on delay of the cooling system after power failure.

SPECIFICATIONS

Model	BEZ1J1
Old Model	BFUR-25-504
Temperature Range	-10 ~ -25 °C
Ambient Temperature	10~32°C
Capacity (L/Cu. Ft.)	528 / 18.66 (264x2 / 9.33x2)
Interior Dimensions (WxDxH) mm	651x632x635x2
Exterior Dimensions (WxDxH) mm	900x818x1875
Weight	160 kgs
Controller	Microprocessor
Display	Digital
Sensor	NTC
Voltage and Frequency	220V±10%, 50/60Hz
Power	230 W
Electric Current	1.6 A
Power Consumption (kWh/24h)	3.4
High / Low Temp. Alarm	Yes
Power Failure Alarm	Yes, 8h
Sensor Error Alarm	Yes
Controller Error Alarm	Yes
Door Ajar Alarm	Yes
Abnormal Ambient Temp. Alarm	Yes
Refrigeration Type	Direct Cooling
Defrost	Manual
Compressor (Brand/pcs)	Chinese Brand / 2
Refrigerant / Weight	R290 / 86gx2
Door (pcs)	Foamed Solid Door / 2
Fixed Shelf (pcs)	4
Drawer (pcs)	18
Interior Cabinet Material	Coated Steel
Exterior Cabinet Material	Coated Steel
Insulation Material	PURF (Φ95mm)

Door Lock	Yes
Test Hole (pcs)	2
Castors (pcs)	4
Leveling Feet (pcs)	2
USB Data Download Port	Yes
Remote Alarm Port	Yes
RS485 Port	Optional
Temperature Datalogger	Optional
Temperature Printer	Optional
Temperature Chart Recorder	Optional
Package	Carton box with pallet
Shipping Weight	190 kgs
Shipping Size (WxDxH)	930x980x2020
Shipping Volume	1.84 CBM
Alt Name	-25°C Double-door Biomedical Freezer



FEATURES

Microprocessor control, ensure good inner temperature uniformity, accuracy is 0.1°C

Double outside doors and two independent freezer chambers.

HC green refrigerant is energy-saving and environmentally friendly.

Wide available voltage range: 220V±10%.

Security

Safety door lock and controller password to prevent unauthorized access.

Built-in backup battery to display temperature and alarms when power failure or system error.

Visual and audible alarm system.

Power failure protection: turn-on delay of the cooling system after power failure.

Controller error protection: the cooling system will remember the normal working cycle and keep working depending on this memory when the controller or two sensors failed.

Humanized design

Drawers for easy storage.

Castors with stoppers for easy moving and fixation.

APPLICATIONS

The -25°C medical deep freezers are designed to store vaccines, blood plasma, reagents, and many other biological materials which are widely used in research institutions, clinics, and medical fields.

DOUBLE DOOR FREEZER BEZ1Y1

-40°C DOUBLE-DOOR BIOMEDICAL FREEZER



Microprocessor control, ensure good inner temperature uniformity, accuracy is 0.1°C

Double outside doors and two independent freezer chambers.

HC green refrigerant is energy-saving and environmentally friendly.

Wide available voltage range: 220V±10%.

Security

Safety door lock and controller password to prevent unauthorized access.

Built-in backup battery to display temperature and alarms when power failure or system error.

Visual and audible alarm system.

Power failure protection: turn-on delay of the cooling system after power failure.

SPECIFICATIONS

Model	BEZ1Y1
Old Model	BFUR-40-308
Temperature Range	-20 ~ -40°C
Ambient Temperature	10~32°C
Capacity (L / Cu. Ft.)	179x2 / 6.32x2
Interior Dimensions (WxDxH) mm	466x636x625x2
Exterior Dimensions (WxDxH) mm	720x830x1870
Weight	138 kgs
Noise	49 dB
Controller	Microprocessor
Display	Digital
Sensor	NTC
Voltage and Frequency	220V±10%, 50/60Hz
Power	345W
Electric Current	3.2 A
Power Consumption (kWh/24h)	6
High / Low Temp. Alarm	Yes
Power Failure Alarm	Yes, 8h
Sensor Error Alarm	Yes
Controller Error Alarm	Yes
Door Ajar Alarm	Yes
Abnormal Ambient Temp. Alarm	Yes
Refrigeration Type	Direct Cooling
Defrost	Manual
Compressor (Brand/pcs)	CUBIGEL / 2
Refrigerant / Weight	R290 / 90g
Door (pcs)	Foamed Solid Door / 2
Shelf (pcs)	4
Drawer (pcs)	12
Interior Cabinet Material	Coated Steel
Exterior Cabinet Material	Coated Steel

Insulation Material	PURF (895mm)
Door Lock	Yes
Test Hole (pcs)	2
Castors (pcs)	4
Leveling Feet (pcs)	2
USB Data Download Port	Yes
Remote Alarm Port	Yes
RS485 Port	Optional
Temperature Datalogger	Optional
Temperature Printer	Optional
Package	Carton box with pallet
Shipping Weight	178 kgs
Shipping Size (WxDxH) mm	780x970x2000
Shipping Volume	1.51 CBM
Alt Name	-40°C Double-door Biomedical Freezer



FEATURES

Microprocessor control, ensure good inner temperature uniformity, accuracy is 0.1°C

Double outside doors and two independent freezer chambers.

HC green refrigerant is energy-saving and environmentally friendly.

Wide available voltage range: 220V±10%.

Security

Safety door lock and controller password to prevent unauthorized access.

Built-in backup battery to display temperature and alarms when power failure or system error.

Visual and audible alarm system.

Power failure protection: turn-on delay of the cooling system after power failure.

Controller error protection: the cooling system will remember the normal working cycle and keep working depending on this memory when the controller or two sensors failed.

Humanized design

Drawers for easy storage.

Castors with stoppers for easy moving and fixation.

APPLICATIONS

The -40 °C medical deep freezers are designed to store vaccines, blood plasma, reagents, and many other biological materials which are widely used in research institutions, clinics, and medical fields.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada
Email: info@biolabscientific.com | Website: www.biolabscientific.com