



BIOLOGICAL INDICATOR INCUBATOR

BIOLOGICAL INDICATOR INCUBATOR BGH1P1 BGH1P2

BIOLOGICAL INDICATOR INCUBATOR

Biological indicator incubators are designed for temperature incubation of the EO biological indicators. Both of them are compact, tabletop incubators.



LCD display.

Users can set the incubating temperature and time.

Exact correspondence of the set and actual temperature.

It is easy to set up and use.

The Incubator has many wells for placement of the biological indicator vials and the wells can be custom-made.

SPECIFICATIONS

Model	BGH1P1	BGH1P2
Temp. control range	RT. +5 °C~80 °C	RT. +5 °C~100 °C
Timer range	1 min~99 h 59 min	
Temp. control accuracy	±0.5 °C	
Display accuracy	±0.1 °C	
Heating time (25 to 57 °C)	≤6 min	
Dimension (DxWxH) mm	110x150x80 mm	120x152x112 mm
Weight	0.5 kg	0.85 kg
Temp. stability @57 °C	±0.35 °C	
Alt Name	Biological Indicator Incubator	



BGH1P1



BGH1P2

ACCESSORIES FOR PURCHASE

No	Name	Type	Description
1	Block	A	15xΦ10 mm
2	Block	B	15xΦ12 mm
3	Block	C	6xΦ15 mm
4	Block	D	6xΦ16 mm
5	Block	E	24xΦ8.8 mm
6	Block	F	18xΦ9 mm

BIOLOGICAL INDICATOR INCUBATOR BFA1DG1

BIOLOGICAL INDICATOR INCUBATOR

Biological Indicator Incubator is supporting equipment for bio-indicator. It is small size, light weight, and is suitable for pressure steam sterilizer biological indicator, ethylene oxide sterilization biological indicator, and other biological indicator sterilization effect detection and cultivation.



Unique designed. Small size, light weight, portable, and suit on various occasions.
LCD display. Temperature and time display simultaneously.
Auto fault detect and buzzer alarm. Temperature calibration function.
24V DC power supply input, low energy consumption. Built-in over-temperature protection device, safe and reliable.
Variety of standard sample blocks for choice. Convenient for replacement. Block can be customized.
Timing function. Time range from 1 to 999min.

SPECIFICATIONS

Model	BFA1DG1
Old Model	BIBI-201
Temp. Control Range	R.T. +5°C~100°C
Temp. Setting Range	5°C~100°C
Temp. Stability @ 56°C	±0.5°C
Temp. Display Accuracy	0.1°C
Heating Speed	<6min (20°C to 56°C)
Time Range	1sec999sec or 1min999min
Voltage	DC 24V adapter
Power	60W
Dimension	W.110 x D.156 x H.92mm
Net Weight	1kgs
Alt Name	Biological Indicator Incubator

ACCESSORIES FOR PURCHASE

No	Accessories code	Spec	Dia. of hole	Name	Block dimension
1	MiniP-A	φ10mmx15	10.5mm	Flat bottom	71x47x32mm
2	MiniP-B	φ12mmx12	12.5mm	Flat bottom	71x47x32mm
3	MiniP-C	φ15mmx6	15.5mm	Flat bottom	71x47x32mm
4	MiniP-D	φ16mmx6	16.5mm	Flat bottom	71x47x32mm
5	MiniP-E	φ9mmx18	9.5mm	Flat bottom	71x47x32mm



1



2



3



4



5

FEATURES

Unique designed. Small size, light weight, portable, and suit on various occasions.

LCD display. Temperature and time display simultaneously.

Auto fault detect and buzzer alarm. Temperature calibration function.

24V DC power supply input, low energy consumption. Built-in over-temperature protection device, safe and reliable.

Variety of standard sample blocks for choice. Convenient for replacement. Block can be customized.

Timing function. Time range from 1 to 999min.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com