



NATURAL CONVECTION INCUBATOR

NATURAL CONVECTION INCUBATOR BGI1Q1 TO BGI1Q5

NATURAL CONVECTION INCUBATOR



Technical Advantage Performance and Features

- Temperature Range: Amb+5°C ~65°C .
- P.I.D temperature controller provides accurate and reliable temperature control.
- Natural convection heating allows the sample temperature to be uniform, suitable for sterilization, powder drying and high temperature storage.
- Extended Life Silicone Rubber Gasket provides excellent sealing and long service life, but is easily replaced when the time for replacement is needed.

Convenience

- Volume(10L~210L).
- Inner chamber is made from corrosion-resistant mirror stainless steel.
- Round curved inner angle is easy to clean.

SPECIFICATIONS

Model	BGI1Q1	BGI1Q2	BGI1Q3	BGI1Q4	BGI1Q5
Old Model	BINC-7801	BINC-7802	BINC-7803	BINC-7804	BINC-7805
Electrical Requirement	220V 50Hz				
Temperature Range	Amb+5~65℃				
Display Resolution	0.1℃				
Ambient Temperature	+5~35℃				
Power Consumption	85W	125W	250W	550W	900W
Inner Glass Door	None		Has		
Viewing Window	Has		None		
Chamber Volume	16L	35L	50L	115L	220L
Interior Dimension (WxDxH ,mm)	270x260x232	360x325x300	400x330x380	520x450x495	650x500x680
Exterior Dimension (WxDxH ,mm)	507x397x347	597x464x417	665x667x600	785x587x715	915x657x870
Shelves	2PCS			3PCS	
Alt Name	Natural Convection Incubator				

FEATURES

Technical Advantage Performance and Features

- Temperature Range: Amb+5°C ~65°C .
- P.I.D temperature controller provides accurate and reliable temperature control.
- Natural convection heating allows the sample temperature to be uniform, suitable for sterilization, powder drying and high temperature storage.
- Extended Life Silicone Rubber Gasket provides excellent sealing and long service life, but is easily replaced when the time for replacement is needed.

Convenience

- Volume(10L~210L).
- Inner chamber is made from corrosion-resistant mirror stainless steel.
- Round curved inner angle is easy to clean.
- Anti-skid shelf design, easy to operate by single hand.

Safety

- Auto Start Feature after power loss/return.
- Temperature deviation alarm.
- Over current protection alarm.
- Independent Over-temperature protection meets DIN 12880 International standard requirements provides you double protection.(Option)

Options:

- Intelligent programmable temperature controller
- Independent temperature-limiting Alarm system
- RS485 connector

NATURAL CONVECTION INCUBATOR BGI2F1 TO BGI2F8

HEATING INCUBATOR

Heating Incubator - natural convection:

The heating incubator provides stable and controllable temperature environment through precise temperature control. It adopts natural convection mode, stable airflow and small temperature fluctuation. It is widely used in bacterial culture, fermentation, breeding, constant temperature culture and other tests.

Heating Incubator - forced convection:

The heating incubator provides stable and controllable temperature environment through precise temperature control. It adopts forced convection mode, full airflow exchange, good temperature uniformity and small fluctuation. It is widely used in bacterial culture, fermentation, breeding, constant temperature culture and other tests.



Intelligent:

It provides two options: colorful touch screen controller and LCD controller. It is easy to operate. (Professional type LCD controller)

With preset power on, standby and shutdown functions.

Parameters such as multi-stage temperature, circulating wind speed, time and heating rate can be set and programmed at the same time, simplifying the complicated test process and realizing automatic control and operation.

Specialization:

Tested and manufactured using the international DIN-12880-2007 standard.

Provide professional temperature control, high temperature control accuracy and small temperature uniformity error.

The sample can be viewed through the internal glass door without affecting the t

SPECIFICATIONS

Model	BGI2F1	BGI2F2	BGI2F3	BGI2F4
Old Model	BIGP-6201	BIGP-6202	BIGP-6203	BIGP-6204
Type	Touch screen			
Capacity (L)	34L	54L	124L	222L
Temp Range	RT+5 - 80°C			
Stability	±0.2°C			
Uniformity (at 37°C)	±0.8°C			
Display Resolution	0.1°C			
Max number of shelves	2(5)	2(6)	2(10)	2(16)
Max load per shelf	20Kg			
NW	44Kg	53Kg	79Kg	108Kg
Timing Range	1 - 5999mins			
Interior Dimension WxDxH (mm)	320x340x320	400x360x415	520x480x490	650x540x650
Exterior Dimension WxDxH (mm)	610x520x580	690x468x640	810x588x755	940x658x910
Electrical Requirement	AC220V/50Hz			
Power Consumption	250W	300W	550W	700W
Alt Name	Heating Natural convection Incubator			
Model	BGI2F5	BGI2F6	BGI2F7	BGI2F8
Old Model	BIGP-6301	BIGP-6302	BIGP-6303	BIGP-6304
Type	LCD Controller			
Capacity (L)	34L	54L	124L	222L

Temp Range	RT+5 - 80°C			
Stability	±0.2°C			
Uniformity (at 37°C)	±0.8°C			
Display Resolution	0.1°C			
Max number of shelves	2(5)	2(6)	2(10)	2(16)
Max load per shelf	20Kg			
NW	44Kg	53Kg	79Kg	108Kg
Timing Range	1 - 5999mins			
Interior Dimension WxDxH (mm)	320x340x320	400x360x415	520x480x490	650x540x650
Exterior Dimension WxDxH (mm)	610x520x580	690x468x640	810x588x755	940x658x910
Electrical Requirement	AC220V/50Hz			
Power Consumption	250W	300W	550W	700W
Alt Name	Heating Natural convection Incubator			



BGI2F1 BGI2F2 BGI2F3 BGI2F4



BGI2F5 BGI2F6 BGI2F7 BGI2F8

FEATURES

Intelligent:

It provides two options: colorful touch screen controller and LCD controller. It is easy to operate. (Professional type LCD controller) With preset power on, standby and shutdown functions.

Parameters such as multi-stage temperature, circulating wind speed, time and heating rate can be set and programmed at the same time, simplifying the complicated test process and realizing automatic control and operation.

Specialization:

Tested and manufactured using the international DIN-12880-2007 standard.

Provide professional temperature control, high temperature control accuracy and small temperature uniformity error.

The sample can be viewed through the internal glass door without affecting the temperature inside the box (option)

Stackable to save lab space.

Flexible shelf design for efficient use of interior space.

Safety:

Protection of equipment: The second set of temperature limit alarm system conforms to international standards. When the heating is out of control or exceeds the maximum limit temperature, the heating is automatically cut off, and the sound and light alarm reminds the operator. Ensure that the equipment operates safely without accidents.

Protection of key components: The key electrical components are equipped with over-current, over-temperature, overload and other safety protection to prevent accidental equipment.

Protection of the sample: When the temperature inside the box is higher or lower than the set temperature, the alarm will start to cut off the heater, and the sound and light will remind the operator to protect the sample from normal test without accident.

Protection for users: The cabinet and door are specially insulated to make the surface temperature of the cabinet low, ensuring the operator's safety and no accidents.

Provide fault information: When the device fails, the display will display fault information to ensure that the fault information is clear at a glance.

Humanized design:

Adopting direct heating system, the heating speed is fast and the control precision is high.

PID control technology, high control precision and small temperature fluctuation.

Available in Chinese and English menus to meet different language needs, with °C/°F conversion.

The height of the shelf is adjustable to meet different cultivation needs.

Professional stacking: Tool design, the machine can be stacked, saving lab space and improving the use efficiency (same specification).

Convenient data processing:

The touch screen type standard with a USB Interface, which can record the change status of the temperature parameters. The LCD screen is option for USB Interface.

It can be equipped with RS232 data Interface, which can realize remote control of the machine through software (option).

RS-232 and USB can be selected one of them.

Safety:

Protection on Instruments: Comply International standard secondary temp limiting alarm system. When the heating is out of control or exceeds the maximum limit temperature, the heating is automatically cut off with sound and light alarm, ensure operating is safe without any accident.


Protection on key components: Key components are equipped with over-current, over-temperature, overload and other safety protection to prevent accident.

Protection on samples: When the temperature inside the box is higher or lower than the set temperature, the alarm will start to cut off the heater, with sound and light alarm to remind the operator to protect the sample from normal test without accident.

Protection on operator: The cabinet and door are specially insulated to make the surface temperature of the cabinet low, ensuring the operator's safety and no accidents.

Breakdown message provided: When the instrument breakdown, the message will show on the screen to help operator clearly check.

Colorful intelligent touch screen:



Advanced Color Intelligent Touch Screen Control


1. 4.3 inch touch screen, intelligent touch control, real-time display of parameters, simple and convenient operation.
2. Quick setting of temperature, time and other parameters can be carried out.
3. It has the function of program setting. It can be programmed in 7 segments, 63 steps, 9 steps and 1-99 hours and 59 minutes per segment.
4. With touch screen automatic locking function to prevent non-related personnel from disoperation.



Professional LCD Controller


1. Intelligent program control with high brightness LCD screen, button operation and real-time display of parameters.
2. Quick setting of temperature, time and other parameters can be carried out.
3. It has the function of program setting. It can be programmed in 7 segments, 63 steps, 9 steps and 1-99 hours and 59 minutes per segment.

Precise temperature control:




The uniformity of the temperature inside the incubator chamber is $\leq \pm 10$ degree , so that all samples are heated evenly.


Note: The stability and uniformity are the result under steady state.



Program control mode, linear temperature rise control.



Temperature fluctuation inside the incubator chamber is ± 0.2 degree, which ensures the stability of the experiment.



Program control mode, Step heating control.



Professional duct design:

With a unique duct design, the use of large impeller fans, fast temperature rise and fall, stable temperature control, good temperature uniformity.

The circulating fan has adjustable speed, middle and low grades, so as to avoid the volatilization of samples due to excessive air flow during the test.


Famous brand fan, high efficiency, low noise, energy saving and environmental protection.



Stainless steel inner liner:

304 stainless steel, mirror polishing, strong anti-corruption ability.

Large arc angle design, no dead angle, easy cleaning and maintenance.




Ultraviolet sterilization system (option)

Ultraviolet lamp is located on the upper wall of the box body. It can disinfect the box body regularly and kill the plankton bacteria in the circulating air of the box body effectively so as to prevent the pollution during cell culture.



No overturning system:

Wire shelves with no overturning system to always operate safely.



Temperature test hole:

External detection sensor can real-time detect the temperature inside the box through the test hole to ensure that the temperature inside the box is accurate and reliable.



Temperature limit alarm system:

When the temperature control system is out of control and the temperature exceeds the limit temperature, the heating is automatically interrupted to ensure the safety of testing.



Sample temperature sensor (optional):

Optional sample temperature sensor, real-time detection of sample temperature, so that the temperature is more real and reliable.

Double Convection Model:

Fan power can be adjusted from 0% (equivalent to natural convection) - 100% four gears, which can meet the training requirements of different airflow.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com