

PRODUCT CATALOG



WHEELCHAIR





WHEELCHAIR BJP1E1

ELECTRIC LIFT PATIENT TRANSFER WHEELCHAIR

Wheelchair is mainly used as a manually operated or power-driven device designed with double cross-shaped brackets, which enhance the safety of the structure. In the meantime, adjustable armrests, quick disassembly of footrest, positioning of Controller and other functions reflect the user-friendly design, and provide great convenience for the user.



This is a kind of patient lift it is electric lift height of sling can be adjustable

SPECIFICATIONS

Model	BJP1E1
Old Model	BHBD-1103
Material	Iron, Plastic, Nylon
Maximum loading weight	150 kg
Lifting Range	25 cm, from 40 cm to 65 cm.
Wheel	Two front wheels are with brake
Door width, chair can pass it	At least 55 cm
It suites for bed	Height of bed from 11 cm to 63 cm
Waterproof level	IP44
Dimensions	123x72.5x54.5 cm
Rated power	96 W
Voltage	DC 24 V
Power supply	Battery, rechargeable
Alt Name	Electric lift patient transfer Wheelchair

APPLICATIONS

Patient transfer, patient lift, toilet-bath chair, Patient Indoor-outdoor locomotion

2

WHEELCHAIR BJP1C1

ELECTRIC LIFT PATIENT TRANSFER WHEELCHAIR

A wheelchair is mainly used as a manually operated or power-driven device designed with double cross-shaped brackets, which enhance the safety of the structure. In the meantime, adjustable armrests, quick disassembly of footrest, positioning of Controller and other functions reflect the user-friendly design, and provide great convenience for the user.



Thickened aluminium alloy body strong bearing capacity

180° opening and closing, easy to realize the transfer of various scenes Electric motor, one-button button control, easy lifting operation, convenient and quick displacement

Soft and comfortable armrest, comfortable to use

360-degree universal wheel, with locking mechanism, shifting is more secure PU leather seat cushion, waterproof, can be showered, hollow design,a toilet can be placed below, Easy to extract

SPECIFICATIONS

Model	BJP1C1
Old Model	BHBD-1101
Material	Iron, Plastic
Maximum loading weight	150 kg
Lifting Range	25 cm, from 40 cm to 65 cm.
Wheel	Two front wheels are with brake
Door width, chair can pass it	At least 55 cm
It suites for bed	Height of bed from 11 cm to 63 cm
Waterproof level	IP44
Dimensions	123x72.5x54.5 cm
Rated power	96 W
Voltage	DC 24 V
Power supply	Battery, rechargeable
Alt Name	Electric lift patient transfer Wheelchair

APPLICATIONS

Patient transfer, patient lift, toilet-bath chair, Patient Indoor-outdoor locomotion

WHEELCHAIR BJP1D1

ELECTRIC LIFT PATIENT TRANSFER WHEELCHAIR

Wheelchair is mainly used as a manually operated or power-driven device designed with double cross-shaped brackets, which enhance the safety of the structure. In the meantime, adjustable armrests, quick disassembly of footrest, positioning of Controller and other functions reflect the user-friendly design, and provide great convenience for the user.



Thickened aluminium alloy body, strong bearing capacity

180° opening and closing, easy to realize the transfer of various scenes Electric motor, one-button button control, easy lifting operation, convenient and quick displacement

Soft and comfortable armrest, comfortable to use. 360-degree universal wheel, with locking mechanism, shifting is more secure

PU leather seat cushion, waterproof, can be showered, hollow design,a toilet can be placed below, Easy to extract

SPECIFICATIONS

Model	BJP1D1
Old Model	BHBD-1102
Material	Iron, Plastic
Maximum loading weight	150 kg
Lifting Range	33 cm, from 40 cm to 73 cm.
Wheel	Two front wheels are with brake
Door width, chair can pass it	At least 55 cm
It suites for bed	Height of bed from 11 cm to 72 cm
Waterproof level	IP44
Dimensions	131x72.5x54.5 cm
Rated power	96 W
Voltage	DC 24 V
Power supply	Battery, rechargeable
Alt Name	Electric lift patient transfer Wheelchair

APPLICATIONS

Patient transfer, patient lift, toilet-bath chair, Patient Indoor-outdoor locomotion

WHEELCHAIR BJP1B1 TO BJP1B4

ELECTRIC TOILET LIFT

Electric Toilet lift is mainly suitable for the elderly, pregnant women, disabled and other people who have inconvenient movements



Adjustable Lifting: Adjustable lifting angle for seat height comfort at different heights

Strong Thrust:Double push strength up to 200kg, satisfying 150kg weight and sitting freely

Safe Voltage :DC 24V safe voltage, ultra-low energy consumption

Silent Operation: The whole process of silent operation ensures the comfort of sitting

Self-protection System: When a unilateral failure occurs, the machine automatically starts the self-protection function and stops running

One-button Reset:After use, long press the switch key to reset with one button, while locking other buttons to ensure safe use

SPECIFICATIONS

Model	BJP1B1	BJP1B2	BJP1B3	BJP1B4
Old Model	BHBD-1201	BHBD-1202	BHBD-1203	BHBD-1204
Material	Iron, Plastic			
Seat height	From 45 to 75 cm			
Weight Capacity	150 kg			
Noise	Almost silent electric motor when operation			
Inclination angle	15°-16°			
Size	57 cm width, 65 cm length, 47 cm height			
For person	Bariatric person, elderly person, patients disabled person, and pregnant women			
Rated power	96 W / 2 A			
Voltage	DC 24 V			
Power source	Electric power	Battery power, rechargeable battery	Electric	power
Alt Name	Electric Toilet lift			









APPLICATIONS

Nursing home, rehabilitation center, Hospital

WHEELCHAIR BJP1F1

ELECTRIC LIFT PATIENT TRANSFER WHEELCHAIR

Wheelchair is mainly used as a manually operated or power-driven device designed with double cross-shaped brackets, which enhance the safety of the structure. In the meantime, adjustable armrests, quick disassembly of footrest, positioning of Controller and other functions reflect the user-friendly design, and provide great convenience for the user.



Thickened aluminium alloy body, strong bearing capacity 180° opening and closing, easy to realize the transfer of various scenes Electric motor, one-button button control, easy lifting operation, convenient and quick displacement Soft and comfortable armrest, comfortable to use

360-degree universal wheel, with locking mechanism, shifting is more secure PU leather seat cushion, waterproof, can be showered, hollow design, a toilet can be placed below, Easy to extract

SPECIFICATIONS

Model	BJP1F1
Old Model	BHBD-1104
Material	Iron, Plastic, Nylon
Maximum loading weight	150 kg
Lifting Range	Seat: 33 cm, from 40 cm to 73 cm. Upper lifting: 29 cm
Wheel	Two front wheels are with brake
Door width, chair can pass it	At least 55 cm
It suites for bed	Height of bed from 11 cm to 72 cm
Waterproof level	IP44
Dimensions	198x72.5x54.5 cm
Rated power	96 W
Voltage	DC 24 V
Battery	Two Batteries
With upper lifting vest	Yes
With individual soft cushion	Yes
Power supply	Battery, rechargeable
Alt Name	Electric lift patient transfer Wheelchair

APPLICATIONS

Patient transfer, patient lift, toilet-bath chair, Patient Indoor-outdoor locomotion

6

WHEELCHAIR BJP1G1

ELECTRIC LIFT PATIENT TRANSFER WHEELCHAIR

Wheelchair is mainly used as a manually operated or power-driven device designed with double cross-shaped brackets, which enhance the safety of the structure. In the meantime, adjustable armrests, quick disassembly of footrest, positioning of Controller and other functions reflect the user-friendly design, and provide great convenience for the user.



Thickened aluminum alloy body, strong bearing capacity 180° opening and closing, easy to realize the transfer of various scenes Electric motor, one-button button control, easy lifting operation, convenient and quick displacement

Soft and comfortable armrest, comfortable to use

360-degree universal wheel, with locking mechanism, shifting is more secure PU leather seat cushion, waterproof, can be showered, hollow design, a toilet can be placed below, Easy to extract

SPECIFICATIONS

Model	BJP1G1
Old Model	BHBD-1105
Material	Steel, PU
Maximum loading weight	150 kg
Lifting Range	Seat: 30 cm, from 40 cm to 70 cm.
Wheel	Two front wheels are with brake
Door width, chair can pass it	At least 58 cm
It suites for bed	Height of bed from 9 cm to 70 cm
Waterproof level	Yes, IP44, top grade waterproof
Control	Remote control
Handles	All foldable
Dimensions	55x65x73 cm
Rated power	96 W
Voltage	DC 24 V
Power supply	Battery, there is a button on battery to power it on/off
Alt Name	Electric lift patient transfer Wheelchair

APPLICATIONS

Patient transfer, patient lift, toilet-bath chair, Patient Indoor-outdoor locomotion

WHEELCHAIR BJP1H1

ELECTRIC LIFT PATIENT TRANSFER WHEELCHAIR

Wheelchair is mainly used as a manually operated or power-driven device designed with double cross-shaped brackets, which enhance the safety of the structure. In the meantime, adjustable armrests, quick disassembly of footrest, positioning of Controller and other functions reflect the user-friendly design, and provide great convenience for the user.



Thickened aluminium alloy body, strong bearing capacity 180° opening and closing, easy to realize the transfer of various scenes Electric motor, one-button button control, easy lifting operation, convenient and quick displacement

Soft and comfortable armrest, comfortable to use

360-degree universal wheel, with locking mechanism, shifting is more secure PU leather seat cushion, waterproof, can be showered, hollow design, a toilet can be placed below, Easy to extract

SPECIFICATIONS

Model	BJP1H1
Old Model	BHBD-1106
Material	Steel, PU, Silicone cushion
Maximum loading weight	150 kg
Lifting Range	Seat: 30 cm, from 40 cm to 70 cm.
Wheel	Two front wheels are with brake
Door width, chair can pass it	At least 58 cm
It suites for bed	Height of bed from 9 cm to 70 cm
Waterproof level	Yes, IP44, top grade waterproof
Control	Remote control
Handles	All foldable
Dimensions	65x57x73 cm
Rated power	96 W
Voltage	DC 24 V
Power supply	Battery, there is a button on battery to power it on/off
Alt Name	Electric lift patient transfer Wheelchair

APPLICATIONS

Patient transfer, patient lift, toilet-bath chair, Patient Indoor-outdoor locomotion



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada Email: info@biolabscientific.com | Website: www.biolabscientific.com