



IMMERSION ULTRASONIC VIBRATION PLATE

IMMERSION ULTRASONIC VIBRATION PLATE BJR1I1 TO BJR1I7

IMMERSION ULTRASONIC VIBRATION PLATE



MCU-SWEEP

Degassing

Constant power output

Work-conserving

1. Made of thickened SUS304 or SUS316L stainless steel,chrome coated on vibration surface,double pulse welding,stronger sealing performance;

2. Automatic frequency tracking, MCU-SWEEP constant power output ultrasonic generator drive, ultrasonic cleaning performance is uniform and strong;

3. Adopt industrial grade high Q value transducer, imported high strength glue bonding,ultrasonic cleaning conversion efficiency is higher;

4. 24 hours working available,suitable for mass production and continuous work;

5. Strict producing and aging process,the whole machine is passed 2500V high vol

SPECIFICATIONS

Model	BJR1I1	BJR1I2	BJR1I3	BJR1I4
Ultrasonic Power(W)	600	900	1200	1500
Number of transducer(PCS)	12	18	24	30
Inner tank Dimension (mm)	350X300X100	450X300X100	550X400X100	580X400X100
Frequency Working (Khz)	25/28/40/68/80/100132/170/200KHz.			
Maximum Temperature(°C)	80°C			
Material	304/316L stainless steelThickness:2.0-3.0mmVibrating plate chrome coatedCable length:5m (customised)			
Working Voltage	110V10%,60KHz220V10%,50/60KHz			
Alt Name	Immersion ultrasonic vibration plate			

Model	BJR1I5	BJR1I6	BJR1I7
Ultrasonic Power(W)	1800	2100	2400
Number of transducer(PCS)	36	42	48
Inner tank Dimension (mm)	600X500X100	650X550X100	700X600X100
Frequency Working (Khz)	25/28/40/68/80/100132/170/200KHz.		
Maximum Temperature(°C)	80°C		
Material	304/316L stainless steelThickness:2.0-3.0mmVibrating plate chrome coatedCable length:5m (customised)		
Working Voltage	110V10%,60KHz220V10%,50/60KHz		
Alt Name	Immersion ultrasonic vibration plate		



BJR1I1



BJR1I2



BJR1I3



BJR1I4



BJR115



BJR116



BJR117

FEATURES

MCU-SWEEP



Degassing



Constant power output



Work-conserving



1. Made of thickened SUS304 or SUS316L stainless steel,chrome coated on vibration surface,double pulse welding,stronger sealing performance;
2. Automatic frequency tracking, MCU-SWEEP constant power output ultrasonic generator drive, ultrasonic cleaning performance is uniform and strong;
3. Adopt industrial grade high Q value transducer, imported high strength glue bonding,ultrasonic cleaning conversion efficiency is higher;
4. 24 hours working available,suitable for mass production and continuous work;
5. Strict producing and aging process,the whole machine is passed 2500V high voltage testing and CE,FCC,ROSH and so on specifications;
6. Different size, power and frequency can be made according to customers actual requirements.

APPLICATIONS

Ultrasonic vibrating plates are mainly used in cleaning, emulsification, polymerization, crushing and other fields. Through high-frequency vibration and micro-strong impact, it can effectively remove dirt, oil stains, rust spots and other impurities on the surface of items, improving cleaning efficiency and quality. In emulsification applications, the vibration and cavitation of ultrasonic waves can be used to promote the dissolution, dispersion, and mixing between solids and liquids, and liquids and gases in the liquid, forming a uniformly dispersed emulsion. In addition, ultrasonic vibrating plates are also used in polymerization reactions and crushing applications in chemical synthesis, polymer polymerization, material science, medicine, food and other fields. In addition, ultrasonic vibrating plates have other applications such as promoting plant growth and increasing plant yields.



Biolab Scientific Ltd.

Trillium Executive Center, East Tower, 675 Cochrane Dr, Markham, Ontario L3R 0B8, Canada

Email: info@biolabscientific.com | Website: www.biolabscientific.com